



Intumex® Wrap - Fire Stopping Wrap

General

Intumex® Wrap is an expanding fire stopping tape. Flexibility is given by the possibility to make any wrap diameter on site. Furthermore, it is the most space-efficient solution for plastic pipe penetrations.

Area of Application

Intumex® Wraps are tested for walls and floors for soft and mortar-system penetrations and for all common plastic piping materials, such as PVC, PP, PE, and combustible insulated metal pipes.

System Advantages / Customer Benefits

- ⇒ Flexible
- ⇒ Quick and easy installation
- ⇒ Resistant to atmospheric influences (light, heat, frost, UV radiation, humidity)

Technical Data

Colour	anthracite grey
Consistency	flexible wrap
Weight	2.5 ± 0.3 kg/m ²
layer thickness	2.5 mm ± 0.3 mm
Reaction to fire (DIN 4102)	B1, normal combustible
Expansion temperature	approx. 150 °C

Test Certificate / Approval

- ⇒ EN 1366-3 (cable/cable bundles, pipes), EN 13501-2/classification reports

Packaging

- ⇒ Thickness : 2.5 mm
- ⇒ Coil : length 18 m, width 50 mm
- ⇒ Packaging : Carton
Carton core diameter 120 mm
Subject to change!

Storage requirements

- ⇒ Store in cool and dry conditions

Safety Instructions

- ⇒ Keep out of reach of children
- ⇒ Avoid contact with food and beverages
- ⇒ Please refer to the safety data sheet for additional advice

